

## MATERIALS LIST:

- A. 2" SERVICE CLAMP
- B. 2" CORPORATION STOP MALE THREAD INLET BY COMPRESSION OUTLET
- C. 2" COPPER WATER SERVICE TUBING EXTENDED BEYOND PAVEMENT
- D1. 2" BALL VALVE, SPL WW-275
- D2. 2" BALL VALVE, SPL WW-275
- E. 2" COPPER SERVICE TUBING
- F. 2" BRASS COUPLING COMPRESSION TO MALE IPT
- G. 2" BRASS TEE
- H. 2" BRASS CLOSE-NIPPLE
- I. 2" ANGLE METER STOP; SERVICE TUBING INLET x FLANGED OUTLET
- J. 2" BRASS NIPPLE
- K. 2" BRASS ELBOW
- L. 2" LOCKABLE CURB STOP FEMALE IPT INLET BY COMPRESSION OUTLET
- M. 2" BRASS COUPLING SERVICE TUBING TO MALE IPT
- N. RECTANGULAR METER BOX AND COVER, SPL WW-145A
- O. BRASS ADAPTER (2" x 1 ½") FOR 1 ½" METER ONLY
- P. WATER METER. LENGTH 13", (PURCHASED FROM AUSTIN WATER)
- Q. 2" COPPER SERVICE TUBING (PRIVATE PLUMBING PER CODE)
- R. CUSTOMER CUT-OFF VALVE
- S. CUSTOMER VALVE BOX AND LID

## NOTES:

- SERVICE CLAMP SHALL BE WRAPPED COMPLETELY WITH 8 MIL. POLYETHYLENE FILM.
- 2. BRANCH CONNECTIONS AND ALL ANGLE METER STOPS MUST BE INSTALLED PRIOR TO ANY METER INSTALLATION.
- 3. TOP OF BOXES SHOULD BE 1" ABOVE GROUND.
- 4. PIPING AND TUBING IN STREET RIGHT-OF-WAY SHALL BE BEDDED IN GRANULAR MATERIALS AS REQUIRED BY SECTION 510.3 (14) OF THE CITY OF AUSTIN STANDARD SPECIFICATIONS; BACKFILL ABOVE GRANULAR BEDDING AS REQUIRED BY SECTION 510.3 (25).
- 5. BOX MUST BE BEHIND CURB NEXT TO PROPERTY LINE OR EASEMENT AND OUT OF VEHICULAR TRAFFIC AREA AND SIDEWALK.
- 6. BALL VALVE "D1" SHALL NOT BE LOCATED UNDER SIDEWALK, CURB, OR PAVEMENT, AND NOT BE LOCATED MORE THAN 24" HORIZONTALLY FROM METER BOX OR 36" BELOW FINAL GRADE.
- 7. COPPER SERVICE SHALL BE COPPER TUBING SIZE ANNEALED SEAMLESS TYPE "K" MEETING ASTM B88 WITH NO SWEAT OR SOLDERED JOINTS.

## **RECLAIMED WATER:**

FOR RECLAIMED WATER SERVICES AND METERS, ALL RECLAIMED TUBING SHALL BE MANUFACTURED PURPLE TUBING. ALL OTHER TUBING AND APPURTENANCES SHALL BE MANUFACTURED PURPLE IF AVAILABLE. ALL TUBING AND FITTINGS THAT ARE NOT AVAILABLE FROM THE MANUFACTURER IN PURPLE SHALL BE PAINTED PURPLE PER SPL WW-3C. ALL BURIED DI AND CI PIPE AND FITTINGS SHALL ALSO BE WRAPPED IN PURPLE POLYETHYLENE PER SPL WW-27D. ALL COVERS SHALL HAVE "RECLAIMED WATER" CAST INTO THEM.

CITY OF AUSTIN AUSTIN WATER		$1\frac{1}{2}$ " - 2" METER INSTALLATION SHOWING OPTIONAL BYPASS	
Kathi L. Flowers	05/18/2016 ADOPTED	THE ARCHITECT/ENGINEER ASSUMES RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD.	STANDARD NO. 520-AW-04